

TIGER TRACTOR



Standard Product Features:

- One-step operator entry & exist
- Low front hood and nose section
- Low center of gravity
- Robust unibody frame
- Heavy duty front & rear plates
- V6 gasoline engine
- Automatic transmission
- Hydrostatic power steering
- Four wheel disc brakes
- Recessed head lights
- Combination brake & tail lights
- Driver bucket type seat
- Non slip surface on floor boards
- Quality paint finish

TC-30/60L Low Profile Tow Tractor

The Low Profile Tow Tractor is a proven product with 3,000 to 6,000 lb (13.3 to 26.7 kN) drawbar pull. The tractor is available with multiple engine packages to meet various environmental conditions. The unit is equipped with steel unibody frame construction for durability and reliability. The unit has excellent steering capability and maneuverability. An enclosed cab and other options are available.

TIGER TRACTOR • METRO CROWN

100 SW Scherer Road • Lee's Summit, MO 64082 (816) 525-3900 • Toll Free (877) 428-4437 • Fax (816) 525-8878 www.tigermfg.com



Product Specifications TC-30/60L

Specifications are subject to change without notice

 Model
 DBP
 GVW

 TC-30L
 3,000 lb (13.3 kN)
 4,530 lb (2,055 kg)

 TC-50L
 5,000 lb (22.2 kN)
 6,700 lb (3,039 kg)

 TC-60L
 6,000 lb (26.7 kN)
 7,600 lb (3,447 kg)

- 1) Drawbar Pull (DBP) is measured on dry level concrete surface
- 2) Gross Vehicle Weight (GVW) & Drawbar Pull (DBP) tolerance +/- 3%
- 3) Available force to push is lower than the DBP depending on the application

Dimensions:

Length (less coupler) 105.0 inches 2,667 mm Width 55.0 inches 1,397 mm Height (less cab) 57 0 inches 1.448 mm 77.5 inches 1,969 mm Height (with cab) Wheelbase 65.0 inches 1,651 mm **Ground Clearance** 6.5 inches 165 mm

Turning Radius:

Two wheel steer 120.0 inches 3,048 mm

Frame:

Type Unibody steel frame construction with heavy

duty front & rear plates

Engines:

Type Gasoline, V-6, 6 cylinder

LPG, V-6, 6 cylinder Diesel, in-line, 4 cylinder

Cooling Systems:

Type Water-cooled, radiator

Fuel System:

Type LPG, gasoline, diesel

Capacity LPG:

33.5 Lb ICC tank Gasoline & diesel:

16 U.S gal 60.0 L

Air Intake System:

Type Single stage dry element

Exhaust System:

Type Single muffler with rear exhaust discharge

Transmission:

Type Automatic transmission three-speed with

torque converter & oil cooler

Steer Axle:

Type Heavy duty steer axle with knuckles & arms

Drive Axle:

Type Heavy duty differential drive axle with double

reduction gearbox

Suspension:

Front Leaf springs
Rear Rigid mounted

Tires:

Front 6.50 x 10 Rear LT225/75R16

Steering System:

Type Hydrostatic steering system with steering

wheel, column & hydraulic valve connected to

a power cylinder on the front steer axle

Braking System:

Type (Service) Brake pedal & linkage connected to a power

booster & master cylinder with dual (split) ports connected to front & rear caliper/disc brakes

Type (Park) Lever operated independent park brake

Electrical System:

Type 12 volt negative ground with heavy duty starter,

alternator & battery

Lighting Head lights, brake/tail lights & reverse/backup

lights

Warning Horn (steering wheel button)

Instrument Panel:

Switches Ignition switch (anti-restart) & head light switch

Gauges Engine coolant temperature, engine oil

pressure, voltmeter, fuel level & hour meter

Standard Driver black vinyl covered bucket type

adjustable seat

Options:

Seat:

Cab Overhead guard
Heater & defroster Beacon light
Turn signals Backup alarm
Passenger seat Seat belts

Fire extinguisher Various hitches

Custom painting

Factory Customization

Maintains OSHA compliance

· Contact your local dealer for details

Other options available upon request

